

Specification Sheet

Part Number: T30R2M4



Standard Cable Tie, 5.8" Long, UL Rated, 30lb Tensile Strength, PA66, Red, 1000/pkg

Article Number	111-03056
Type	T30R
Color	Red (RD)
Features & Benefits	<ul style="list-style-type: none">• Inside serrations allow for strong hold on cables and wire bundles.• Head design provides high tensile strength with very low insertion force.• Bent tail ensures a quick and simple installation.
Quantity Per	bag

Product Description

T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description	Standard Cable Tie, 5.8" Long, UL Rated, 30lb Tensile Strength, PA66, Red, 1000/pkg
Global Part Name	T30R-PA66-RD
Minimum Tensile Strength (Imperial)	30.0
Minimum Tensile Strength (Metric)	135.0
Length L (Imperial)	5.8
Length L (Metric)	148.0
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.14
Width W (Metric)	3.6
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.38
Bundle Diameter Max (Metric)	35.0

Thickness T (Metric)

1.1

Material

Polyamide 6.6 (PA66)

Material Shortcut

PA66

US MIL SPEC

MS3367-5-2

SAE-AS33671

Flammability

UL 94 V2

Halogen free

Yes

Operating Temperature (Metric)

-40°F to +185°F (-40°C to +85°C)

ROHS Complaint

Yes

Certification/Specification WEB

CAGE Code 53421 UL-ZODZ.E64139

UL Recognized (US)

Yes

UL Listed (US and Canada)

Yes

UL Recognized (US and Canada)

Yes

Package Quantity(Imperial)

1000

Package Quantity (Metric)

1000

Customs Number

3926909987

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)