



Material

- ①Clamp: Brass,Ni plated
- ②Terminal screw: Steel Zinc plating "-" slot type
- ③Wire guard solder pin: Brass,Tin plated
- ④Terminal housing: Thermoplastic (UL94V-0) , GREY

Electrical cULus

Voltage rating: 600V
 Current rating: 65A
 Wire range:
 Solid wire(AWG): 6-22
 Stranded wire(AWG): 6-22
 Torque(Lb-In): 8.7Lb-In
 Screw: M4
 Wire strip length: 6-7mm
 Withstanding Voltage: 2.2KV
 Operating temperature: -40°C to +115°C
 Soldering temperature: 250°C±10°C/5 Sec
 Safety Approval: cULus

RoHS compliant



Scale	1:1					Date	Name	Customer-No.
TOLERANCE						Drawn	16.12.2010	Schulz
X.	±0.50					Approved	16.12.2010	Gerber
X.X	±0.30							
X.XX	±0.10							
DIM	TOL	①	UL Update	23.03.2017	C.Bakula			
X.°	±1°	②	Drawn	16.12.2010	Schulz			
Angle	TOL	Id.	Modification	Date	Name	Replace		Sheet

ASSMANN WSW-No.
A-TB000-V405

Drawing-No.
ASS 4115D CO rev01

Replace Sheet