



RESISTANCE @ +25°C = 1 Ω ± 15%
 MAXIMUM STEADY STATE CURRENT = 20 AMPS
 RESISTANCE @ MAXIMUM CURRENT = 0.015 Ω NOMINAL
 DIM "D" = 1.200" MAXIMUM
 DIM "T" = 0.300" MAXIMUM
 DIM "L" = 0.900" MINIMUM
 DIM "S" = 0.310" NOMINAL
 LEAD GAUGE = 18 AWG

SEE MANUFACTURING SPECIFICATION (LAYER 1)

| | | | |
|-----|---|----------|-----|
| "A" | DIM "D" WAS 0.900" MAXIMUM & DIM "L" WAS 1.0" MINIMUM | 07/14/09 | DD |
| --- | ISO RELEASE | 10/29/03 | DD |
| REV | REVISION RECORD | DATE | APP |

| | | |
|----------|---------------|---|
| SCALE | NONE | U.S. SENSOR CORP. 1832 W. COLLINS AVE. ORANGE, CA 92867 714-639-1000 www.ussensor.com |
| DRAWN BY | T. SOMERVILLE | |
| DATE | 03/04/90 | |
| REV. | "A" | |
| LAYER | 0 OF 2 | |
| | | INRUSH CURRENT LIMITER |
| | | P/N ST1R020B |