



- 注 1. APPLICABLE WIRE IS AWG #16(1.25sq) ~ #18(0.75sq) OF STRANDED CABLE.
 2. APPLICABLE CRIMPING MACHINE AND CRIMPING CONDITIONS (CRIMP HEIGHT etc.) WILL BE SPECIFIED ACCORDING TO AWG # OR WIRE APPLIED.
 3. ONE PACKAGE CONSISTS OF 100 PCS.
 4. THIS PRODUCT IS ASSEMBLED WITH TJ50A-41S-※.
 5. REFER TO ATAI-E3050 FOR CRIMP QUALITY STANDARDS.

1	COPPER ALLOY	CONTACT AREA : GOLD PLATING 0.76µm TERMINAL AREA : TIN PLATING UNDER PLATING : NICKEL PLATING
NO.	MATERIAL	FINISH , REMARKS

UNITS mm		SCALE 5 : 1	COUNT △	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
HIROSE ELECTRIC CO., LTD.				APPROVED : NM. NISHIMATSU 14.06.03	DRAWING NO. EDC3-128056-00		
				CHECKED : NM. NISHIMATSU 14.06.03	PART NO. TJ50A-1618SCA		
				DESIGNED : KG. OKITA 14.06.03	CODE NO. CL236-3103-6-00		
				DRAWN : KG. OKITA 14.06.03	△ 1/1		