

4-Port DisplayPort KVM Switch with Audio, Cables and USB 3.0 SuperSpeed Hub

MODEL NUMBER: **B004-DPUA4-K**



Control 4 DisplayPort computers using one DisplayPort monitor, USB keyboard and USB mouse. Connect USB 3.0 peripherals, such as hard drives and webcams, and share them between computers.

Description

The desktop B004-DPUA4-K 4-Port DisplayPort KVM Switch lets you access, control, boot and reboot four DisplayPort computers using one DisplayPort monitor, USB keyboard and USB mouse. Switching among DisplayPort computers is quick and simple using keyboard hotkeys or buttons on the unit.

You can also plug microphones and speakers into the 3.5 mm mini-stereo jacks, and the two-port USB 3.0 SuperSpeed hub allows you to connect peripherals, such as a webcam, flash drive, printer or scanner, and share them among computers. Because the audio and USB 3.0 hub ports can be accessed independently, you can, for instance, use a printer connected to the hub to print data from one computer while also listening to music from another computer.

All necessary cables are included. The B004-DPUA4-K supports digital video resolutions up to 2560 x 1600 (including 1080p), 2-channel stereo audio and data transfer rates up to 5 Gbps. The monitor's EDID information is sent to the connected computer when selected.

The B004-DPUA4-K is easy to set up with no software to install and supports Windows, Mac, Linux and Sun. The USB 3.0 hub is backward-compatible with USB 2.0 and USB 1.1 devices.

Features

Access and Control Up to 4 Computers with One KVM Switch

- Switch among computers using keyboard hotkeys or front-panel buttons
- Monitor's EDID information sent to connected computer when selected
- Auto Scan feature cycles among computers at regular intervals for at-a-glance observation of activity
- Supports DisplayPort 1.1

Highlights

- Connect peripherals to built-in 2-port USB 3.0 hub
- Switch among computers via front buttons or keyboard hotkeys
- Supports digital video resolutions up to 2560 x 1600
- Supports Displayport 1.1
- Includes all necessary DisplayPort, USB 3.0 and audio cables

System Requirements

- DisplayPort-enabled monitor
- USB keyboard and mouse
- Speaker and microphone with 3.5 mm mini-stereo plugs (for audio)
- Computer with USB port (need USB 3.0 port for USB 3.0 speed)
- Computer with 3.5 mm mini-stereo jacks (for audio)
- Compatible with all major operating systems

Package Includes

- B004-DPUA4-K 4-Port DisplayPort KVM Switch
- (4) DisplayPort cables, 6 ft.
- (4) USB 3.0 Type-A to Type-B cables, 6 ft.
- (4) 3.5 mm mini-stereo cables, 6 ft.
- External power supply (Input: 100/240V, 50/60 Hz, 0.8A; Output: 9V, 2A)
- Universal plug adapters (NEMA



Independent Audio Switching

- 3.5 mm mini-stereo speaker and microphone jacks allow sharing of audio equipment among computers
- Listen to audio files on one computer while accessing another computer
- Supports 2-channel stereo audio

Independent USB 3.0 Peripheral Sharing

- 2-port USB 3.0 SuperSpeed hub allows connection of peripherals, such as webcams, flash drives, printers and scanners
- Print documents from one computer while accessing another computer
- Supports USB 3.0 data transfer rates up to 5 Gbps
- Backward compatible with USB 2.0 and USB 1.1 devices

Compatible with All Major Operating Systems

- Easy to set up with no software or drivers to install
- Supports digital video resolutions up to 2560 x 1600, including 1080p
- Works with Windows, Mac, Linux and Sun
- All necessary cables included

1-15P, CEE 7/16, BS1363, and AS3112)

- Owner's manual

Specifications

| OVERVIEW | |
|---|---|
| UPC Code | 037332188632 |
| Users | 1 |
| AC Adapter | Input: 100-240V, 50/60Hz, 0.8A Output: 9V, 2A |
| Technology | USB 3.0 (SuperSpeed); USB (all versions); DisplayPort (all types); Stereo Audio |
| INPUT | |
| Voltage Compatibility (VAC) | 100; 110; 120; 127; 200; 208; 220; 230; 240 |
| External Power Supply Input Specs (V / Hz / A) | 100-240V / 50/60Hz / 0.8A |
| External Power Supply Output Specs (V / A) | 9V/ 2A |
| External Power Supply Cord Length (ft.) | 6 |
| External Power Supply DC Barrel Connector Specs | OD: 5.5 x 2.1 x 10mm, Positive Pin, Negative Sleeve |
| External Power Supply Plug(s) | NEMA 1-15P North America; CEE 7/16 Schuko; BS 1363 UK; AS/NZS 3112 Australia |
| External Power Supply Certifications | CE; FCC; UL; cUL; TUV; GS; BS; RCM; CB |



| USER INTERFACE, ALERTS & CONTROLS | |
|--|--------------------------------|
| LED Indicators | Red (USB); White (Selected PC) |
| PHYSICAL | |
| Shipping Dimensions (hwd / in.) | 7.40 x 6.20 x 10.60 |
| Shipping Dimensions (hwd / cm) | 18.80 x 15.75 x 26.92 |
| Shipping Weight (lbs.) | 5.90 |
| Shipping Weight (kg) | 2.68 |
| Unit Packaging Type | Box |
| Unit Dimensions (hwd / in.) | 1.8 x 8.1 x 3.9 |
| Unit Weight (lbs.) | 2.1 |
| Unit Weight (kg) | 0.95 |
| Material of Construction | SECC |
| Color | Black |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32 to 104 F (0 to 40 C) |
| Storage Temperature Range | -4 to 140 F (-20 to 60 C) |
| Relative Humidity | 0%-90% RH, Non-Condensing |
| BTUs | 22.2 BTU/Hr |
| Power Consumption (Watts) | 6.5 |
| COMMUNICATIONS | |
| IP Remote Access | No |
| CONNECTIONS | |
| Ports | 4 |
| PC/Server Connections | USB; DisplayPort |
| Side A - Connector 1 | (4) DISPLAYPORT (FEMALE) |
| Side A - Connector 2 | (4) USB 3.0 B (FEMALE) |
| Side A - Connector 3 | (8) 3.5MM (FEMALE) |
| Side B - Connector 1 | DISPLAYPORT (FEMALE) |
| Side B - Connector 2 | (2) USB 3.0 A (FEMALE) |
| Side B - Connector 3 | (2) USB A (FEMALE) |
| Side B - Connector 4 | (2) 3.5MM (FEMALE) |
| Computer Keyboard and Mouse Interface | USB |



| | |
|--------------------------------------|--|
| Computer Monitor Interface | Displayport |
| Console Keyboard and Mouse Interface | USB |
| Console Monitor Interface | Displayport |
| Connector Plating | Nickel |
| FEATURES & SPECIFICATIONS | |
| Port Selection | Pushbutton; Hotkey |
| Max Supported Video Resolution | 2560 x 1600 @60Hz |
| Displayport Specification | 1.1 |
| USB Hub Ports | Yes |
| Number of USB Hub Ports | 2 |
| USB Specification | USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps) |
| Driver Required | No |
| CERTIFICATIONS | |
| Certifications | Tested to CE, FCC, RoHS, REACH |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 3-year limited warranty |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>